

WaterSentinel®

WSI-1

REFRIGERATOR REPLACEMENT FILTER



Manufactured by: Aquamor, LLC. Temecula, CA.

This filter should not be used with water that is microbiologically unsafe or of unknown quality, without adequate disinfection before and/or after the filter.

This filter has been tested by the manufacturer against ANSI/NSF Standard 42 for the reduction of chlorine taste and odor.

ADVANCED FILTRATION TECHNOLOGY

This WaterSentinel® refrigerator water filter contains a compressed carbon block which provides tremendous capacity to remove and/or reduce impurities and sediment that may be present in your drinking water. The carbon block has millions of active sites on its surface and within the structure which can absorb impurities like a sponge, and can adsorb and hold other types of impurities on its surface like a magnet. Additionally, this filter can catalytically breakdown other impurities very similar to the way a catalytic converter works in your automobile. These processes ensure that you are getting the cleanest and best tasting water possible.

This economical filter will provide you with fresh and clean tasting water and ice cubes.

THIS FILTER FITS IN PLACE OF:

- The Whirlpool® WHKF-IMTO, WHCF-IMTO. It is also known as 55616 and Omni Pure CL10RO
- GE® GXITQR, GXITD, GXITQ, GXRTQ
- Waterpik® IF30, IF-30, IF30A, IF-30A, IF31, IF-31, IF-35 - Aquapure APIL3, APIL3R
- American Plumber® WIC, WIC6A, WIC-6A, WICS, WICSa, 155083
- Culligan® IN-1
- Pentek® GS10, GS-10, GS10B, GS-10-B, IC10IL, IC-10IL
- Hydroflow® - GS10, GS-10, GS10RO, GS-10-RO, GS10AS, GS-10AS, GS-10-AS GoldSeries - GS10, GS-10, GS10RO, GS-10-RO, GS10AS, GS-10AS, GS-10-AS
- Omnipure® CL10ROT33, CL-10RO-T33, K2533 Omni R200, R-200, R400, R-400
- Cuno® ILIM01, IL-IM-01
- Whirlpool® 4378411
- Samsung® EF9603, EF-9603, WSF100, WSF-100 LG BL9808, BL-9808
- Daewoo® DD7098, DD-7098
- Hotpoint® BL9808, BL-9808

Guaranteed to fit by WaterSentinel®

FILTER FEATURES:

- Economical alternative to expensive substitutes
- Delivers clean, clear water that looks and tastes great
- Will reduce chlorine taste and odor that may be present in your drinking water
- Designed to provide up to six months of life or 300 gallons
- Does not remove minerals which may be beneficial to health

SPECIFICATIONS:

Flow Rate:	.5 gpm (1.89 lpm)
Operating Temperature:	33°-100°F (0.6°-38°C)
Min Operating Pressure:	30 psi (207 kPa)
Max Operating Pressure:	100 psi (689 kPa)
Life:	6 months or 300 gallons (1,136 liters)

*WHIRLPOOL IS A REGISTERED TRADEMARK OF WHIRLPOOL COMPANY