


Installation Quick Start Guide for WSF-2

Important Installation Instructions

- 1. Turn off the ice maker in your refrigerator (refer to owners manual if needed).
- Locate the filter cup inside your refrigerator, and remove by turning to the left multiple turns.
- 3. Remove old filter and discard.
- Wash the filter cup with warm water and liquid soap then dry.
- Insert filter into filter cup, o-ring end should be facing up.
- Insert cup with filter into refrigerator and turn to the right until cup is seated firmly.
- 7. Turn on refrigerator ice maker.
- Run water from the dispenser for 5minutes at .5 gpm (about 2.5 gallons) to clear the system and prevent sputtering.

Note: Initial flow rate may be slower than expected. Full flow rate should be restored within 24-36 hours.

To reset Filter Indicator light, press and hold the reset button on the dispenser until the light flashes (up to 15 seconds).



Specifications

Flow Rate:	.5 gpm (1.89 lpm)
Operating Temperature:	33°-100°F (0.6°-38°C)
Operating Pressure:	30-100 psi (207-689 kPa)
Life:	6 Months or 200 gallons (757 liters)



This WSF-2 is Certified by IAPMO R&T against NSF/ANSI Standard 42 for the reduction of Chlorine taste and odor. Refer to Performance Data Sheet for complete list of claims.

For further questions or assistance please call (866) 218-8473. Warning: To reduce the risk of property damage from water leakage, the filter bypass plug MUST be used when a filter replacement cartridge is not installed. For cold water applications only, Do not use with water that is microbiologically unsafe or of unknown ouality without adequate disinfection before or after the system. Protect from freezino.

REPLACE FILTER EVERY 6 MONTHS, OR IF BAD TASTE OR ODOR OCCUR.
Installation shall comply with applicable state and local regulations.
The risk associated with small parts can cause choking if swallowed.
Keep children away from small parts during the replacement of the water filter.

Aquamor, LLC, 42188 Rio Nedo, Temecula, CA 9/2023 • BEV 2307 www.watersentinelfilters.com

P/N 803165