



## Installation Quick Start Guide for WSG-6

### Important Installation Instructions

1. Remove the filter from the manifold by twisting the filters to the left about 1/3 turn.
2. Remove sanitary cap from new filter. Insert the new filter into the manifold by turning the filter to the right about 1/3 turn until the filter stops. The filter will rise up into the manifold as it is turned. **DO NOT OVER TIGHTEN.**
3. Turn faucet on to allow trapped air to purge out of the system.  
**Note:** The system may make noise during this process.
4. Inspect your system for leaks.
5. Flush about 2.5 gallons of water through the system (up to 5 minutes depending on flow rate) to displace any excess carbon fines and trapped air within the filter that may be present.
6. Turn faucet off and inspect the system for any leaks.
7. To reset your timer, please refer to your system owner's manual for specific instructions.

<b>Micron Rating:</b>	0.5 Micron
<b>Flow Rate:</b>	0.5 gpm (1.89 lpm)
<b>Operating Temperature:</b>	33-100°F (0.6°-38°C)
<b>Min Operating Pressure:</b>	35 psi (241 kPa)
<b>Max Operating Pressure:</b>	100 psi (689 kPa)
<b>Life:</b>	6 months or 300 gallons (1,136 liters)



This WSG-6 is Tested and Certified by NSF International against NSF/ANSI Standard 42 for the reduction of chlorine taste and odor.



This WSG-6 is Certified by IAPMO R&T against NSF/ANSI Standard 42 for the reduction of Chlorine taste and odor. Refer to Performance Data Sheet for complete list of claims.

### For further questions or assistance please call (866) 218-8473.

**Warning:** To reduce the risk of property damage from water leakage, the filter bypass plug **MUST** be used when a filter replacement cartridge is not installed. For cold water applications only. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Protect from freezing. **REPLACE FILTER EVERY 6 MONTHS, OR IF BAD TASTE OR ODOR OCCUR.**

Installation shall comply with applicable state and local regulations.

The risk associated with small parts can cause choking if swallowed.

Keep children away from small parts during the replacement of the water filter.

Aquamor, LLC, 42188 Rio Nedo, Temecula, CA

[www.watersentinelfilters.com](http://www.watersentinelfilters.com)