




Installation Quick Start Guide for WSL-2

Important Installation Instructions


1. Locate existing filter and remove it by turning it counter clockwise as shown in the graphic. The filter will eject slightly with a clicking sound.



2. Remove sanitary cap from new filter.




3. Insert the new filter into the refrigerator filter receptacle. With the handle in the vertical position, push the new filter into the housing until it stops. When inserting the new filter, twist the handle slightly left to right, while pushing inward. Rotate the filter clockwise a full 1/4 turn until you feel it stop. Ensure filter is fully installed in refrigerator head a full 1/4 turn. This is required to activate the internal valve inside the refrigerator. If the filter is not turned a full 1/4 turn the valve will not fully open and may cause the water flow to be slow, or even cause the valve to make a chattering noise during use.



4. Run water from the dispenser for 5 minutes at .5 gpm (about 2½ gallons) to clear the system and prevent sputtering.

Note: Initial flow rate may be slower than expected. Full flow rate should be restored within 24-36 hours.



5. Reset your 'change filter' light (if your fridge has one).

Reset



6. Check filter for any leaks. If leaks are detected, uninstall and reinstall the filter as instructed above.



Specifications

Flow Rate:	.5 gpm (1.89 lpm)
Operating Temperature:	33°-100°F (0.6°-38°C)
Operating Pressure:	30-100 psi (207-689 kPa)
Life:	6 Months or 300 gallons (1,136 liters)



This WSL-2 is Tested and Certified by NSF International against NSF/ANSI Standard 42 for the reduction of chlorine taste and odor.



This WSL-2 is Tested and Certified by IAPMO R&T against NSF/ANSI Standards 42, 53 & 372, for the reduction of Chlorine taste and odor, Lead, Cyst, VOC's, Mercury, Asbestos. Refer to Performance Data Sheet for complete list of claims.

For further questions or assistance please call (866) 218-8473.

Warning: To reduce the risk of property damage from water leakage, the filter bypass plug MUST be used when a filter replacement cartridge is not installed. For cold water applications only. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

Protect from freezing. REPLACE FILTER EVERY 6 MONTHS, OR IF BAD TASTE OR ODOR OCCUR.
Systems Certified for cyst reduction may be used on disinfected waters that may contain filterable cysts.

Installation shall comply with applicable state and local regulations.

The risk associated with small parts can cause choking if swallowed.
Keep children away from small parts during the replacement of the water filter.