



Installation Quick Start Guide for WSL-4

Important Installation Instructions

LOCATION 1

1. Pull the cartridge cover down by pressing the sides of the cover for the cover to drop down.
Note: If the top shelf in the refrigerator is in the highest position, please remove your top shelf of your refrigerator in order for the cover to drop all the way down.
2. Pull the water filter down and rotate counter clockwise to remove it. **Note:** Be sure that the filter is completely downward prior to removing it out of the housing head.
3. Remove sanitary cap from new filter.
4. With the filter tabs in the horizontal position, insert the new filter into the housing head, rotate the filter upwards into the housing and close the cartridge cover.
5. Run about 2.5-3 gallons of water from your water dispenser to clear the system and prevent sputtering.
Note: Initial flow rate may be slower than expected. Full flow rate should be restored within 24-36 hours.
6. Check the filter for any leaks. If leaks are detected, uninstall and reinstall the filter as instructed above.
7. If your refrigerator has a water filter indicator light on the display, press and hold the Filter button or the Reset button for 3-5 seconds to reset. If this is unsuccessful, please refer to your refrigerator owner's manual for specific instructions on how to reset your filter light.

LOCATION 2

1. Lift and remove the bin at the bottom of the refrigerator door.
2. Swing the right end of the filter out of the filter compartment and then rotate the filter counter clockwise to remove from housing head by getting a good grip on the filter.
3. Remove sanitary cap from new filter.
4. Insert new filter into housing head and rotate clockwise. Swing filter back into cartridge compartment.
5. Replace the bin on the door.
6. Run about 2.5-3 gallons of water from your water dispenser to clear the system and prevent sputtering.
Note: Initial flow rate may be slower than expected. Full flow rate should be restored within 24-36 hours.
7. Check the filter for any leaks. If leaks are detected, uninstall and reinstall the filter as instructed above.
8. If your refrigerator has a water filter indicator on the display, press and hold the Filter button or the Reset button for 3-5 seconds to reset. If this is unsuccessful, please refer to your refrigerator owner's manual for specific instructions on how to reset your filter light.

Specifications

Flow Rate:	.5 gpm (1.89 lpm)
Operating Temperature:	33°-100°F (0.6°-38°C)
Operating Pressure:	20-100 psi (138-689 kPa)
Life:	6 Months or 200 gallons (757 liters)



This WSL-4 is Tested and Certified by NSF International against NSF/ANSI Standard 42 for the reduction of chlorine taste and odor.



This WSL-4 is Tested and Certified by IAPMO R&T against NSF/ANSI Standards 42, 53 & 372, for the reduction of Chlorine taste and odor, Lead, Cyst, VOC's, Mercury, Asbestos. Refer to Performance Data Sheet for complete list of claims.

For further questions or assistance please call (866) 218-8473.

Warning: To reduce the risk of property damage from water leakage, the filter bypass plug MUST be used when a filter replacement cartridge is not installed. For cold water applications only. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Protect from freezing. REPLACE FILTER EVERY 6 MONTHS, OR IF BAD TASTE OR ODOR OCCUR.

Systems Certified for cyst reduction may be used on disinfected waters that may contain filterable cysts.

Installation shall comply with applicable state and local regulations.

The risk associated with small parts can cause choking if swallowed.

Keep children away from small parts during the replacement of the water filter.