




Installation Quick Start Guide for WSF-2

Important Installation Instructions


- 1** Turn off the ice maker in your refrigerator (refer to owners manual if needed).
- 2** Locate the filter cup inside your refrigerator, and remove by turning to the left multiple turns.
- 3** Remove old filter and discard.
- 4** Wash the filter cup with warm water and liquid soap then dry.
- 5** Insert filter into filter cup, o-ring end should be facing up.
- 6** Insert cup with filter into refrigerator and turn to the right until cup is seated firmly.
- 7** Turn on refrigerator ice maker.
- 8** Run water from the dispenser for 5minutes at .5 gpm (about 2.5 gallons) to clear the system and prevent sputtering.
NOTE: Initial flow rate may be slower than expected. Full flow rate should be restored within 24-36 hours.
- 9** Locate the included Water Filter Replacement Calendar, and place dark circle over the month you installed your new filter. The light circle will indicate your next replacement month (May vary with water conditions and usage).

- 10** To reset Filter Indicator light, press and hold the reset button on the dispenser until the light flashes (up to 15 seconds).



Specifications

Flow Rate:	.5 gpm (1.89 lpm)
Operating Temperature:	33°-100°F (0.6°-38°C)
Operating Pressure:	30-100 psi (207-689 kPa)
Life:	6 Months or 300 gallons (1,136 liters)



For further questions or assistance please call (866) 218-8473.

Warning: To reduce the risk of property damage from water leakage, the filter bypass plug **MUST** be used when a filter replacement cartridge is not installed. For cold water applications only. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Protect from freezing. REPLACE FILTER EVERY 6 MONTHS, OR IF BAD TASTE OR ODOR OCCUR

The risk associated with small parts can cause choking if swallowed. Keep children away from small parts during the replacement of the water filter.