




Installation Quick Start Guide for WSF-7

Important Installation Instructions

- 1 Press the button to the right of the filter to release from mounting head.
- 2 Remove the old filter by pulling straight out.
- 3 Push the new filter in firmly until seated into the mounted head; you will hear a "Click" once it is in place.
- 4 If the filter does not "Click" into place, remove and try again. It may take more force than expected.
- 5 Once seated correctly, flush 3 gallons of water from the dispenser to remove any loose fines and to prime the filter.
NOTE: Initial flow rate may be slower than expected.
Full flow rate should be restored within 24-36 hours.
- 6 To reset Filter Indicator Light, press and hold the reset button on the dispenser until the green light flashes (up to 15 seconds).

Specifications

Flow Rate:	.5 gpm (1.89 lpm)
Operating Temperature:	33°-100°F (0.6°-38°C)
Operating Pressure:	30-100 psi (207-689 kPa)
Life:	6 Months or 400 gallons (1,514 liters)



For further questions or assistance please call (866) 218-8473.

Warning: To reduce the risk of property damage from water leakage, the filter bypass plug MUST be used when a filter replacement cartridge is not installed. For cold water applications only. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Protect from freezing. REPLACE FILTER EVERY 6 MONTHS, OR IF BAD TASTE OR ODOR OCCUR.

Installation shall comply with applicable state and local regulations.
The risk associated with small parts can cause choking if swallowed.
Keep children away from small parts during the replacement of the water filter.