




### Installation Quick Start Guide for WSL-3 Important Installation Instructions

- 1** Push button to open filter cover. 
- 2** Pull cartridge down. Pull out the filter.  
NOTE: If the filter is hard to remove, turn off water supply and relieve pressure at refrigerator door water dispenser before installing new filter. 
- 3** Holding new filter, remove the packaging and end-cap. 
- 4** Insert the new filter into the manifold hole until it stops. 
- 5** Push the cover back up until it clicks into place. 

- 6** Run water from the dispenser for 5 minutes at .5 gpm (about 2½ gallons) to clear the system and prevent sputtering.

NOTE: Initial flow rate may be slower than expected. Full flow rate should be restored within 24-36 hours.



- 7** Reset the indicator light by holding down the LIGHT/FILTER button for 3 seconds.



- 8** Check filter for any leaks. If leaks are detected, uninstall and reinstall the filter as instructed above.



#### Specifications

<b>Flow Rate:</b>	.5 gpm (1.89 lpm)
<b>Operating Temperature:</b>	33°-100°F (0.6°-38°C)
<b>Operating Pressure:</b>	20-100 psi (138-689 kPa)
<b>Life:</b>	6 Months or 300 gallons (1,136 liters)



This WSL-3 is Tested and Certified by NSF International against NSF/ANSI Standard 42 for the reduction of chlorine taste and odor.



This WSL-3 is Certified by IAPMO against NSF/ANSI Standard 42 for the reduction of chlorine taste and odor.

#### For further questions or assistance please call (866) 218-8473.

**Warning:** To reduce the risk of property damage from water leakage, the filter bypass plug MUST be used when a filter replacement cartridge is not installed. For cold water applications only. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Protect from freezing. REPLACE FILTER EVERY 6 MONTHS, OR IF BAD TASTE OR ODOR OCCUR.

Installation shall comply with applicable state and local regulations.

The risk associated with small parts can cause choking if swallowed.

Keep children away from small parts during the replacement of the water filter.