



Installation Quick Start Guide for WSW-3

Important Installation Instructions

- 1** Locate filter below the refrigerator. Slowly turn the cartridge 1/4 turn counter-clockwise and remove. Remove knob from old filter.



- 2** Remove all packaging, and protective cap from new filter.



- 3** Slide knob from old filter onto new filter. Insert filter into refrigerator and turn 1/4 turn clockwise until firmly seated.



- 4** Run water for 3 minutes through the dispenser to flush the filter.

NOTE: Initial flow rate may be slower than expected. Full flow rate should be restored within 24-36 hours.



- 5** Press the light switch (the one that the refrigerator door presses every time you close the door) 5 times within 10 seconds, or if the fridge has a filter button press and hold it for 5-10 seconds.

- 6** Locate the included Water Filter Replacement Calendar and follow the instructions on the label.

Specifications

Flow Rate:	.5 gpm (1.89 lpm)
Operating Temperature:	33°-100°F (0.6°-38°C)
Operating Pressure:	30-100 psi (207-689 kPa)
Life:	6 Months or 300 gallons (1,136 liters)



This WSW-3 is Tested and Certified by NSF International against NSF/ANSI Standard 42 for the reduction of chlorine taste and odor.



This WSW-3 is Tested and Certified by WQA against NSF/ANSI Standard 42 for the reduction of chlorine taste and odor.

For further questions or assistance please call (866) 218-8473.

Warning: To reduce the risk of property damage from water leakage, the filter bypass plug MUST be used when a filter replacement cartridge is not installed. For cold water applications only. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Protect from freezing. REPLACE FILTER EVERY 6 MONTHS, OR IF BAD TASTE OR ODOR OCCUR

The risk associated with small parts can cause choking if swallowed. Keep children away from small parts during the replacement of the water filter.

TST Water, LLC, 42188 Rio Nedo, Temecula, CA
www.watersentinelilters.com