




Installation Quick Start Guide for WSW-5

Important Installation Instructions

1. Locate your existing filter and remove it by pushing the button firmly until the filter pops out.
2. Remove the cap by rotating it on the existing filter counter clockwise.
3. Remove the safety caps from the end of the new filter and discard.
4. Reinstall the cap on the new filter and insert new filter in the refrigerator.

5. Push new filter in firmly until it clicks into place. **DO NOT TWIST OR ROTATE.**

Please note: While the filter end tips may appear different than your old filter, it has been engineered to fit and function properly in your refrigerator. Be sure to align the filter so that the locking pin is located on the left and the centering guide is located on the right. The centering guide will ensure that our filter is aligned properly during installation.



6. Dispense water into glass looking for good water flow. If flow is slow, remove and reinstall filter.
7. Flush 3 Gallons of water through the filter before use.
Note: Initial flow rate may be slower than expected. Full flow rate should be restored within 24-36 hours.
8. Check the filter for any leaks.
9. Reset the filter replacement indicator light by referring to your refrigerator's owner's manual for instructions.

Specifications

Flow Rate:	.5 gpm (1.89 lpm)
Operating Temperature:	33°-100°F (0.6°-38°C)
Operating Pressure:	30-100 psi (207-689 kPa)
Life:	6 Months or 300 gallons (1,136 liters)



This filter is Tested and Certified by NSF International against NSF/ANSI Standard 42 for the reduction of Chlorine, Taste and Odor.



This filter is certified by IAPMO R&T against NSF/ANSI Standard 42, 53, and 372 for the reduction of Chlorine, Taste and Odor, Lead, Cyst, Mercury, Asbestos and VOC's. Refer to Performance Data Sheet for complete list of claims.

For further questions or assistance please call (866) 218-8473.

Warning: To reduce the risk of property damage from water leakage, the filter bypass plug **MUST** be used when a filter replacement cartridge is not installed. Installation shall comply with applicable state and local regulations. For cold water applications only. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Protect from freezing. **REPLACE FILTER EVERY 6 MONTHS, OR IF BAD TASTE OR ODOR OCCUR.**

Installation shall comply with applicable state and local regulations.
The risk associated with small parts can cause choking if swallowed.
Keep children away from small parts during the replacement of the water filter.

Aquamor, LLC, 42188 Rio Nedo, Temecula, CA
www.watersentinel.com