




Installation Quick Start Guide for WSW-1

Important Installation Instructions


1. Remove the old filter

Open the filter cover and locate the arrow label on the base of filter body before the handle. Pay attention to the orientation of the arrow as the new filter arrow will point in same direction. Grab the filter handle with your fingertips and move handle in the direction of the arrow. Depending on refrigerator model, you will either move handle slightly to the right or slightly down until you feel the filter release, then pull filter straight out.



2. Remove the cap

Take the new filter out and remove the filter cap from the new filter. Make sure the O-ring stays in its original position.



3. Install the new filter

While ensuring the arrow label orientation points in the same direction as the old filter (arrow pointing to the right or pointing down), you will align the two small rails on the filter underside into the refrigerator manifold slot and push inward until fully seated.



4. Close the filter cover door

Close the filter cover door completely in order to snap the new filter into place. You might need to apply some pressure to ensure it's properly secured.



5. Flush the water system

Flush the water system. Then reset filter status light following instructions in your owners manual.



Specifications

Flow Rate:	.5 gpm (1.89 lpm)
Operating Temperature:	33°-100°F (0.6°-38°C)
Operating Pressure:	30-100 psi (207-689 kPa)
Life:	6 Months or 200 gallons (757 liters)



This WSW-1 is Tested and Certified by NSF International against NSF/ANSI Standard 42 and 53 for the reduction of Chlorine, Taste and Odor, Endrin, Trichlorobenzene, p-Dichlorobenzene. Refer to Performance Data Sheet for complete list of claims.

EPA Establishment Number:
92705-CA-1



This WSW-1 has been certified by IAPMO R&T to NSF/ANSI Standards 42, 53, 372, 401, P473 & CSAB483.1 for the reduction of Chlorine, Taste and Odor, Microplastics, Turbidity, Particulate Class 1, Lead, Cyst, VOCs, Mercury, Asbestos, Pharmaceuticals (such as DDE1, TCP and Ibuprofen), BPA, PFDA/PFOA. Refer to Performance Data Sheet for complete list of claims.

For further questions or assistance please call (866) 218-8473.

Warning: To reduce the risk of property damage from water leakage, the filter bypass plug **MUST** be used when a filter replacement cartridge is not installed. For cold water applications only. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

Protect from freezing. **REPLACE FILTER EVERY 6 MONTHS, OR IF BAD TASTE OR ODOR OCCUR.**
Systems Certified for cyst reduction may be used on disinfected waters that may contain filterable cysts.

Installation shall comply with applicable state and local regulations.

The risk associated with small parts can cause choking if swallowed.
Keep children away from small parts during the replacement of the water filter.